

LED SURFACE PANEL

POLVENIRA

DATA SHEET



RATED WATTAGE

15W, 24W
25W

ITEM	EMR- 24SPOLV
DRIVER	PHILIPS/EAGLERISE
CHIPS	OSRAM/SANAN
PANEL DESIGN	SURFACE
INPUT VOLTAGE	AC85-265V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.50
LUMINOUS	100-135Lm/W
DIMMABLE	NON
PROTECTION GRADE	IP 65
BEAM ANGLE	180°
COLOR TEMPERATURE	2700\4000 \6500K
POWER SVE	90%
CRI	>80
LIFE TIME	30,000 \ 50,000 H

Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 30,000 H.



FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-of with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
Schools \ Offices \ Banks
HOMES \ Restaurants

