

# LED UP LIGHT



### FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

### APPLICATION :

Showrooms \ Universities  
Schools \ Offices \ Banks  
Factories \ Restaurants



## DATA SHEET

ITEM NO.	EMR 03 UL
RATED WATTAGE	3W,6W,9W, 12W,18W, 24W
DRIVER	PHILIPS\OSRAM\ ZH\EMR
CHIPS	PHILIPS\OSRAM \SAN'AN\EPISTAR
INPUT VOLTAGE	AC 220V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.5 - 0.95
LUMINOUS	100 -135 Lm\W
PROTECTION GRADE	IP 65
BEAM ANGLE	18 °
COLOR TEMPERATURE	2700-4000-6500 K
BODY COLOR	white\, Black\, gray
DIMENSIONS	H 100 x Ø100
BODY MATERIAL	Die-cast aluminium /Stainless Steel Ring
REFLECTOR	OPAL DIFFUSER
LIFE TIME	30.000 - 50,000 H

**Notes:** All components can be customized.

### WARRANTY

3 - 5 YEARS

### PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 30.000 H.



Luminous intensity distribution  
Luminous intensity distribution

