

LED FLOOD LIGHT



FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
Schools \ Offices \ Banks
Factories \ Restaurants



DATA SHEET

RATED WATTAGE	
	100W, 200W, 300W, 400W, 500W, 600W
DRIVER	Chinese Driver
CHIPS	SAN'AN \ EPISTAR
INPUT VOLTAGE	AC 110 - 265V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	0.95
LUMINOUS	100-190 Lm \ w (optional)
PROTECTION GRADE	IP 66
BEAM ANGLE	120° (optional)
COLOR TEMPERATURE	2700-4000-6500 K
OVERVOLTAGE PROTECTION	✓
UNDERVOLTAGE PROTECTION	✓
OVERCURRENT PROTECTION	✓
REFLECTOR	OPAL Lens / Glass Lens (optional)
SURGE PROTECTION	4.5 - 6 - 10 KV (optional)
LIFE TIME	30.000-50,000 H

Notes: All components can be customized.

WARRANTY

2 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-burning Applications.
- Long Life Time of up to 30,000 H.

Luminous Intensity distribution

