

LED PROFILE LIGHT



FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
 Schools \ Offices \ Banks
 Factories \ Restaurants



DATA SHEET

ITEM NO.	EMR - 30 TL
RATED WATTAGE	30 W
DRIVER	PHILIPS\OSRAM\ZH\EMR
CHIPS	PHILIPS\OSRAM\SAN'AN\EPISTAR
INPUT VOLTAGE	AC 110 - 227V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.5 - 0.95
LUMINOUS	100 - 135 Lm\Meter
PROTECTION GRADE	IP 65
BEAM ANGLE	Diffuse
COLOR TEMPERATURE	2700 - 4000 - 6500 K
BODY COLOR	white \ Black \ gray
DIMENSIONS	300 Cm
BODY MATERIAL	Aluminum With Plastic
REFLECTOR	OPAL DIFFUSER
LIFE TIME	30.000 - 50,000 hours

Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-burning Applications.
- Long Life Time of up to 30.000 H.

