

LED LINEAR LIGHT



FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
Schools \ Offices \ Banks
Factories \ Restaurants



DATA SHEET

ITEM NO.	EMR - 7 LL
RATED WATTAGE	36 W
DRIVER	PHILIPS\OSRAM\ZH\EMR
CHIPS	PHILIPS\OSRAM\SAN'AN\EPISTAR
INPUT VOLTAGE	AC 110 - 240V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.5 - 0.95
LUMINOUS	100 -135 Lm\W
PROTECTION GRADE	IP 65
BEAM ANGLE	120°
COLOR TEMPERATURE	2700 - 4000 - 6500 K
BODY COLOR	white \ Black \ gray
DIMENSIONS	121 Cm
BODY MATERIAL	Aluminum With Plastic
REFLECTOR	OPAL DIFFUSER
LIFE TIME	30.000 - 50,000 hours


Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 30.000 H.



LED LINEAR LIGHT



DATA SHEET

Watts	Luminous Flux	CCT	CRI	Profile Size	Finish
84	8070	4000K	>90	65x145mm	○ ● ● ●

Remark: Watts and Luminous flux data is for a Φ 1.2 meter fixture including a non-dimmable driver.

Watts	Luminous Flux	CCT	CRI	Profile Size	Finish
102	9739	4000K	>90	35x95mm	○ ● ● ●

Remark: Watts and Luminous flux data is for a Φ 1.2 meter fixture including a non-dimmable driver.



Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
Schools \ Offices \ Banks
Factories \ Restaurants



PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-burning Applications.
- Long Life Time of up to 30.000 H.



LED LINEAR LIGHT



DATA SHEET

Model	Watts	Luminous Flux	CCT	CRI	Profile Size	Finish
LPL1M	76	6798	4000K	> 90	26x34mm	○ ● ● ● ●
LPLR1M	76	6798	4000K	> 90	36x27mm	○ ● ● ● ●
LPL1MID	177	12960	4000K	> 90	29x45mm	○ ● ● ● ●

Remark: Watts and Luminous flux data is for a Φ1.2 meter fixture including a non-dimmable driver.

Notes: All components can be customized.

WARRANTY 3 - 5 YEARS

FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

APPLICATION :

Showrooms \ Universities
 Schools \ Offices \ Banks
 Factories \ Restaurants



PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-burning Applications.
- Long Life Time of up to 30.000 H.

