

LED POLE LIGHT - Double Arm Decorative Pole

DATA SHEET

ITEM NO.	EMR - 501 LPL
RATED WATTAGE	2 x 50W
DRIVER	SAMSUNG\OSRAM
INPUT VOLTAGE	AC 220 ~ 240 V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.95
LUMINOUS	120 lm/w
PROTECTION GRADE	IP 65
BEAM ANGLE	Narrow / Medium / Wide
COLOR TEMPERATURE	3000K
BODY COLOR	Black - Gray
DIMENSIONS	W 120 x L120 x H 3000 mm
BODY MATERIAL	High purity extruded aluminium
CRI	80
LIFE TIME	50,000 hours

Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 50.000 H.

Luminous intensity distribution



LED POLE LIGHT - Single Arm Decorative Pole

DATA SHEET

ITEM NO.	EMR - 601 LPL
RATED WATTAGE	50W
DRIVER	SAMSUNG\OSRAM
INPUT VOLTAGE	AC 220 ~ 240 V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.95
LUMINOUS	120 lm/w
PROTECTION GRADE	IP 65
BEAM ANGLE	Narrow / Medium / Wide
COLOR TEMPERATURE	3000K
BODY COLOR	Black - Gray
DIMENSIONS	W 120 x L120 x H 3000 mm
BODY MATERIAL	High purity extruded aluminium
CRI	80
LIFE TIME	50,000 hours

Notes: All components can be customized.

WARRANTY

3 - 5 YEARS

PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 50.000 H.

Luminous intensity distribution

