

# LED PROOF STRIP



### FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

### APPLICATION :

Showrooms \ Universities  
 Schools \ Offices \ Banks  
 Factories \ Restaurants



## DATA SHEET

ITEM NO.	EMR- 016 WP
RATED WATTAGE	20W
DRIVER	PHILIPS / EMR
CHIPS	LUMILED-SAMSUNG / SANAN
INPUT VOLTAGE	AC 110~240 V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.5 - 0.95
LUMINOUS	100 -135 Lm\W
PROTECTION GRADE	IP 65
BEAM ANGLE	110°
COLOR TEMPERATURE	2700 - 4000 - 6500 K
BODY COLOR	white \ Black \ gray
DIMENSIONS	L 600mm*W 95mm*H 80mm
IK	10
CRI	80
LIFE TIME	30.000 - 50,000 hours
Lenght	60 cm

**Notes:** All components can be customized.

### WARRANTY

3 - 5 YEARS

### PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 30.000 H.



# LED PROOF STRIP



### FEATURES :

- LED alternative to conventional lamps.
- Contains no mercury or other hazardous Substances.
- No filaments or glass components.
- Full cut-off with no wasted light above the fixture.

### APPLICATION :

Showrooms \ Universities  
 Schools \ Offices \ Banks  
 Factories \ Restaurants



## DATA SHEET

ITEM NO.	EMR- 016 WP
RATED WATTAGE	40W
DRIVER	PHILIPS / EMR
CHIPS	LUMILED-SAMSUNG / SANAN
INPUT VOLTAGE	AC 110~240 V
OPERATING FREQUENCY	50-60 Hz
POWER FACTOR	> 0.5 - 0.95
LUMINOUS	100 -135 Lm\W
PROTECTION GRADE	IP 65
BEAM ANGLE	110°
COLOR TEMPERATURE	2700 - 4000 - 6500 K
BODY COLOR	white \ Black \ gray
DIMENSIONS	L 1200mm*W 95mm*H 80mm
IK	10
CRI	80
LIFE TIME	30.000 - 50,000 hours
Lenght	120 cm

**Notes:** All components can be customized.

### WARRANTY

3 - 5 YEARS

### PRODUCT BENEFITS :

- Variable use at Direct Current and Alternating Current.
- Good all-around Light Emission.
- Ideal for Decorative and Free-bur-ing Applications.
- Long Life Time of up to 30.000 H.

